

# MA2.8s

Light weight, high performance power amplifier

electronics

## features

- Switch mode power supply
- Superior sonic performance
- Light weight
- Advanced protection circuits
- Efficient copper cooling system
- Minimum load switches (MLS™)



## applications

- Live sound reinforcement
- Fixed installations

The MA2.8s is one of a range of power amplifiers that have been designed to combine reliability and high power with sonic excellence. Utilising an advanced switch mode power supply, the amplifier is characterised by a very high power-to-weight ratio in a lightweight, 2U package. The innovative technology at the heart of the MA2.8s enables it to set new standards in terms of sonic accuracy, impact and clarity.

## technical specifications

### MAX OUTPUT POWER

EIA AT 1 kHz AND 1% THD

MLS in 0dB position	
8 PER CHANNEL	1100 W
4 PER CHANNEL	1500 W
2 PER CHANNEL	1700 W
8 BRIDGED	3000 W
4 BRIDGED	3100 W

### MAX OUTPUT VOLTAGE

8Ω LOAD	94 Vrms
PEAK VOLTAGE, NO LOAD	135 V

### DISTORTION

THD 20Hz – 20kHz AND 1 W TO FULL POWER	0.08%
THD AT 1kHz AND –1dB UNDER CLIP	0.03%
DIM AT –3dB UNDER CLIP	0.02%

### HUM AND NOISE

	<-105dB
--	---------

### CHANNEL SEPARATION @ 10kHz

	80dB
--	------

### OUTPUT IMPEDANCE

	60 mΩ
--	-------

### SLEW RATE

	20 V/μs
--	---------

### INPUTS

GAIN SELECTABLE (dB)	20, 23, 26, 29, 32, 35, 38, 41
----------------------	--------------------------------

### IMPEDANCE

	10 kΩ
--	-------

### COMMON MODE REJECTION

	50dB
--	------

### FRONT PANEL

GAIN CONTROLS	31 position detent
INDICATORS: PROTECT	Yellow LED
INDICATORS: CLIP	Red LED
INDICATORS: SIGNAL PRESENT (-40dB)	Green LED

### REAR PANEL

INPUT CONNECTORS	Neutrik Combo
LINK CONNECTOR	XLR-male
CLIP LIMITERS	On/off each channel
MLS SWITCH	0, -2, -4, -5dB
LINK-SWITCH	CH. A-B

### POWER

OPERATION VOLTAGE	130-270V
-------------------	----------

SOFT START	Yes
------------	-----

PEAK INRUSH CURRENT	5 A
---------------------	-----

FULL OUTPUT POWER	180-260 W
-------------------	-----------

MIN START VOLTAGE	175 V
-------------------	-------

115V OPTION	Yes
-------------	-----

### CURRENT DRAW AT 4Ω/230V

QUIESCENT POWER (NO LOAD)	1 A rms
---------------------------	---------

1/8 OF FULL POWER (-9dB)	5 A rms
--------------------------	---------

1/3 OF FULL POWER (-5dB)	11 A rms
--------------------------	----------

AT FULL POWER (0dB) @ 1kHz 1%THD	19 A rms
----------------------------------	----------

### DIMENSIONS


WIDTH	483mm (19ins)
-------	---------------

HEIGHT	88mm (3.5ins) 2U
--------	------------------

DEPTH (incl.handles)	393mm (15.5ins)
----------------------	-----------------

WEIGHT	10kg (22lbs)
--------	--------------

## overall dimensions



Century Point, Halifax Road, Cressex Business Park,  
High Wycombe, Buckinghamshire HP12 3SL, England.  
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669  
E-mail: [info@martin-audio.com](mailto:info@martin-audio.com)  
All information is Copyright © 2003 Martin Audio Ltd.



[www.martin-audio.com](http://www.martin-audio.com)